

## COLOURWATCH VIDEO CABLES



Cross section of cable

### Cable Specification

Orange Polyurethane outer sheath (1.4mm RT)  
Outside Diameter 11mm  
1 x 1.34mm<sup>2</sup> screened pair  
1 x 0.5mm<sup>2</sup> screened pair  
1 x 0.22mm<sup>2</sup> twisted pair  
1 x 1.34mm<sup>2</sup> core  
1 x 75 ohm mini coax  
Water blocked assembly, overall screen & drain wire

### Weight

116 gms/mtr in air  
68 gms/mtr in seawater

ColourWatch video cables have been proven to be tough enough for the harshest diving environments in over many years. The hardwearing polyurethane outer sheath protects video power, information and lighting cores offering clear picture resolution and minimum power loss.

A range of standard lengths are available ready terminated to suit the ColourWatch video systems.

The following Lengths of cable are available, fully terminated (in meters);

50	Part No: CWUC50
100	Part No: CWUC100
200	Part No: CWUC200
300	Part No: CWUC300
Cable Only	Part No: CWUC001

### Topside Connector

Mil-spec 12/16-pin (as per camera requirements).

### Diver Connectors

Camera – 8-pin Subconn  
Light – 2-pin RMG-2-FS

### Y-splice

A hot moulded Y-splice.

